



# PRODUCT DATA SHEET

## 96 Brake Fluid DOT 3 Heavy Duty

### Description

96 Brake Fluid DOT 3 is a premium high quality, heavy duty brake fluid for use in a wide range of brake and clutch applications. It meets the requirements of S.A.E J1703 standard.

### Application

96 Brake Fluid DOT 3 is designed for use in all brake and clutch systems in passenger cars, 4WD's, motorcycle, light and heavy duty commercial vehicles, mining, construction and agricultural equipments that required a non petroleum based DOT 3 brake and clutch hydraulic fluid.

Applications which requiring disc, drum and anti-skid braking systems used in average to high performance vehicles requiring DOT 3 level performance. Recommendations for use include

- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly; this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, thus to remove spills brake fluid immediately without rubbing.
- Check Owners Operators Manual for details

All conventional brake fluids deteriorate during use. It is strongly recommended that 96 Brake Fluid DOT 3 should be changed according to the vehicle manufacturer's advice. In the absence of such advice, a 2 year change period is recommended.

### Advantages

This product has been formulated from mixed polyalkylene glycol ethers together with high performance additives and inhibitors which give ultimate system protection:

- Against the effects of corrosion
- High boiling point temperature to reduce vapour lock.
- Meets the requirements of the SAE J1703 specifications. 96 Brake Fluid DOT 3 is fully compatible with other fluids meeting SAE J1703 DOT 3 however, in order to maintain the superior performance Characteristics of 96 Brake Fluid DOT 3, avoid mixing with other brake fluids products.

### Typical Characteristics

Name	Method	Units	96 Brake Fluid DOT3
Appearance	Visual	-	Bright / Clear
Colour			Red
Physical state			Liquid
Density @ 20C	ASTM D1298	g/cm3	1.04
pH	SAE J1703	pH	8.50
ERBP (Equilibrium Reflux Boiling Point)	SAE J1703	°C	225 min
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	140 min

### Storage

It packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Justinjarell Global Sourcing Sdn Bhd  
No. 15-2, Jalan Temenggung 27/9,  
Mahkota Square, Bandar Mahkota Cheras,  
43200 Cheras, Selangor D.E., Malaysia  
Tel/Fax: +603 9546 7920  
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.