



# PRODUCT DATA SHEET

## AUTOMATIC TRANSMISSION FLUID 96 ATF CVT – EZL 799

### Product Description

96 ATF CVT - EZL 799 is a high performance transmission fluid for automatic transmission (AT) and continuously variable transmission (CVT) applications.

### Benefits

96 ATF CVT - EZL 799 provides the following benefits when used as recommended:

- Excellent flow properties at low start-up temperatures and high operating temperatures.
- Excellent shift performance and vehicle driveability.
- Excellent oxidation stability, less fluid breakdown in high-temperature service.
- Good viscosity stability
- Good wear protection for maximum transmission life.
- Dependable protection against rust and corrosion.

### Application

96 ATF CVT - EZL 799 is designed to meet the specific requirements of selected automated transmissions, including all PROTON vehicles CVT transmissions. It is used in both ATF and CVTF applications.

96 ATF CVT - EZL 799 is recommended for use in Punch VT2/VT3 transmissions, which are used in specific vehicle models made by several Chinese car manufacturers including Great Wall Motors, Changan Auto, Dong Feng, Geely and PROTON car (including SagaBLM FLX / Preve / Exora Bold / Suprima / Iriz / New Pesona. It is also specified for ZF applications requiring a ZF 481336 fluid (ZFST VT1F, CVT unit).

### Properties and Specifications

Property	ATF CVT - EZL 799
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.0
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	39
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	38,000
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1a
Foam, Sequence III, Tendency, ml, ASTM D892	10/0
Foam, Sequence IV, Tendency, ml, ASTM D6082	40/0
Flash Point, Cleveland Open Cup, °C, ASTM D92	184

Typical physical characteristics of 96 ATF CVT - EZL 799 are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd  
No. 15-2, Jalan Temenggung 27/9,  
Mahkota Square, Bandar Mahkota Cheras,  
43200 Cheras, Selangor D.E., Malaysia  
Tel/Fax: +603 9546 7920  
[www.96justinjarell.com.my](http://www.96justinjarell.com.my)



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.