



PRODUCT DATA SHEET

Motorcycle Engine Oil – 4T

**Synthetic
Blend
SAE 20W50
API SN / MA2**

Product Description

96 4T 20W50 Synthetic Blend is an advanced semi synthetic motorcycle oils engineered for all 4-stroke motorcycles. It also helps to provide excellent protection against wear corrosion and rust. It exerts good control against sludge formation and oxidation with the presence of cleanliness additive. The unique feature of shear stability enables the product maintain in grade at wide range of operating temperature. This engine oil also meets the API SN/MA2 the requirements of the industry and OEM specifications required by the motorcycles engines.

Benefits

- Outstanding thermal and oxidation stability under high temperature
- Provides high performance of engine and contributes to fuel efficiency
- Good degree of cleanliness
- Exceptional against wear and corrosion

Application

- Recommend for all types of four-stroke motorcycle modern engines
- Recommend for all standard motorcycle for city go and stop riding conditions

Properties

The base oil's thermal stability, together with a high-performance additive package, ensures the engine is constantly protected against wear and damage, and can handle the stressful conditions of stop-and-go city traffic. The Advance formulation technology gives very high thermal stability performance to the oil which leads to very prolonged oil change interval. The Advance formulation offers maximum protection in very hot and extremely cold climates and severe riding conditions.

Typical Characteristics

96 4T Motorcycle Engine Oil, SAE 20W50		Credentials & Specifications
API Grade	SN MA2	API: SN JASO: MA2
Flash Point, °C	240	
Pour Point, °C	-19	
Viscosity at 40°C, cSt	170.50	
Viscosity at 100°C, cSt	17.90	
Viscosity Index	116.40	

Typical physical characteristics of 96 Motorcycle Engine Oil are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.