



PRODUCT DATA SHEET

Fully Synthetic

CVT Fluid

Continuously Variable Transmission Fluid

Product Description

96 CVT Fluid is a fully synthetic automatic transmission fluid specially formulated for the use in continuously variable transmission (CVT) gearbox. The high-quality synthetic base oil with selected additives has offers an excellent torque transmission and delivers a reliable performance in most CVT equipped vehicles (e.g., prevent slippage). The anti-shudder unique feature has protected the component from vigorous vibration and provide a comfort driving conditions. This product has met the requirements of the industry and OEM specifications required by most automatic transmission vehicles.

Features and Benefits

- Outstanding thermal and oxidation stability
- Good lubricating feature for gear smooth shifting and anti-shudder
- Exceptional protection against corrosion and extreme pressure
- Provides durable transmission prolong component lifetime

Typical Characteristics

Application

- Recommend for most types' passenger and light commercial car where CVT fluids is mandatory for use
- Suitable for applications in both push belt or chain CVT

96 CVT Fluid is made with a proprietary blend of ultra-high performance fully synthetic base stocks fortified with a precisely balanced component system. This feature is supported, not only by meeting but exceeding the toughest industry performance standards.

Performance Standards

- *Toyota CVTF FE/TC
- *Daihatsu Ammix CVT
- *Nissan NS-1/Ns-2
- *Honda HMMF/Z-1 (CVT model)
- *Mitsubishi CVTF-J1/J4/SP-III (CVT)
- *Subaru ECVT/iCVT/iCVT FG
- *Hyundai SP-III/CVTF1/CVT-J1
- *Mini Cooper EZL799
- *Suzuki CVT Green 1/Green 2/Green NS-2/CVTF 3320/CVTF TC.

96 ATF CVT, Automatic Transmission Fluids		Credentials & Specifications
Appearance / Color	Bright / Red	ATF CVT
Flash Point, PMCC, °C	235	
Pour Point, °C, ASTM D97	- 46	
Viscosity at 40°C, cSt, ASTM D445	34.80	
Viscosity at 100°C, cSt, ASTM D445	7.19	
Viscosity Index, ASTM D2270	176.60	
Density @ 15°C (kg/l)	0.847	

Typical physical characteristics of 96 ATF CVT Oil are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS OR IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.