



PRODUCT DATA SHEET

96 Hydraulic Oil AW 68 Anti-Wear

Product Description

Hydraulic Oil AW 68 is formulated by high quality base oil with the selected advanced additive designed for use in hydraulic system which requires high load capability. The anti-wear additive properties enables the component to work properly and last longer. The high protection against the stress and corrosion can reduce the replacing of the component and maintenance cost. Water Separation also can inhibit the sludge and the deposits build up due to the presence of the water.

Benefits

- Outstanding thermal and oxidation to enhance oil drain intervals
- Minimize the wear parts of hydraulic system component to obtain optimize equipment life
- Good filterability to prevent the blockage of the filter even with the presence of water
- Excellent demulsibility performance to prevent cavitation takes place

Application

- Recommended for use in industrial and mobile hydraulic applications
- Suitable use in hydraulic with vane, piston and gear type pump
- Suitable use in agricultural and construction machinery does not require high viscosity index.

Properties

The base oil's thermal stability, together with a high performance additive package, ensures the hydraulic oil is constantly protected against wear and corrosion.

Typical Characteristics

Hydraulic Oil AW 68	
ISO VG	68
Flash Point, °C	226
Pour Point, °C	- 29
Viscosity at 40°C, cSt	68.02
Viscosity at 100°C, cSt	9.723
Viscosity Index	138.0
Appearance	Bright & Clear

Credentials & Specifications

Anti-Wear / AW 68

Typical physical characteristics of 96 Hydraulic Oil AW 68 are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.