



PRODUCT DATA SHEET

MOTOR ENGINE OIL SAE 20W50 API SL/CF

Product Description

96 Motor Engine Oil 20W50 is a superior quality multigrade oil with new conception, formulated with highly refined base stocks and state of the art additive technology.

Benefits

96 Motor Engine Oil 20W50 provides the following benefits when used as recommended:

- Improved fuel economy and filterability
- Extreme control over wear, rust and corrosion to ensure long life of moving parts
- Outstanding lubrication characteristics in all seasons
- Excellent protection against oxidation, foaming, low temperature sludge and high temperature deposits
- Excellent fluidity at low temperature ensures good starting and longer maintenance intervals
- Properly balanced detergency and dispersancy ensures a clean engine and long Oil Drain Intervals

Typical Characteristics

Diesel Engine Oil	20W50
API Grade	SL/CF
Flash Point, °C	232
Pour Point, °C	-25
Viscosity at 40°C, cSt	172.6
Viscosity at 100°C, cSt	18
Viscosity Index	120
Total Base No., Min.	7.3

Application

96 Motor Engine Oil 20W50 is recommended for use in most modern, high powered cars, vans and light trucks including multi valve techniques and those vehicles fitted with or without catalytic convertors, operating under most severe driving conditions. It is also recommended for use in Unleaded, LPG and turbo charged light vehicles, as well as normally aspirated and turbo charged light diesel engines

Properties

96 Motor Engine Oil 20W50 has high level thermal stability which ensures the high resistance to oxidation, preventing premature degradation at high temperature. Shear resistance ensuring good lubrication is used, both in hot and cold weather. It is suitable for engines burning Lead free fuel and completely harmless to catalytic convertors.

Credentials & Specifications

API: SL/CF

Typical physical characteristics of 96 Motor Engine Oil 20W50 are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.