



PRODUCT DATA SHEET

MOTOR ENGINE OIL

SYNTHETIC BLEND
SAE 5W30
API SN/CF

Product Description

96 Motor Engine Oil 5W30 is developed as a synthetic blend engine oil to meet the requirements of almost all the engines in passenger cars running on multiple fuels like Gasoline, Diesel, Bio Diesel, Gasoline-ethanol Mix, LPG & NG. It is particularly suited for turbo charged, multi valve and direct injection engines.

Benefits

96 Motor Engine Oil 5W30 provides the following benefits when used as recommended:

- As a Synthetic Blend engine oil, it provides excellent oxidation stability, low temperature flow properties
- Helps to protect high performance engines from power and performance robbing deposits
- Helps to protect the engine throughout the oil drain interval
- Protection of three-way catalyst poisons by reducing the volatility of the phosphorus in the lubricant.

Application

96 Motor Engine Oil 5W30 designed for use in modern gasoline engines, diesel engines (without particulate filters) and gas engines. And it is also suitable for use with bio diesel and Gasoline – Ethanol blends.

The Synthetic Blend formulation offers maximum protection in very hot and extremely cold climates and severe driving conditions.

Properties

The Synthetic Blend technology gives very high thermal stability performance to the oil which leads to very prolonged oil change interval. Easier starting in cold weather, faster oil flow for engine life by protecting surfaces from wear and by helping to neutralize the corrosive combustion

Typical Characteristics

Diesel Engine Oil	5W30
API Grade	SN/CF
Flash Point, °C	242
Pour Point, °C	-39
Viscosity at 40°C, cSt	60.2
Viscosity at 100°C, cSt	10.5
Viscosity Index	165
Total Base No., Min.	6.9

Credentials & Specifications

API: SN/CF

Typical physical characteristics of 96 Motor Engine Oil 5W30 are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.