



PRODUCT DATA SHEET

Motor ENGINE OIL

**SAE 10W30
API SN CF**

Product Description

Motor Engine Oil 10W30 is a high quality premium engine oils. It is formulated using high quality base oil and the latest additives technologies to provide the robust and anti-wear protection, thermal and oxidation stability and excellent lubrication films of engine parts operating under boundary lubrication. This engine oil also meets the API SN/CF performance and exceeds the requirements of the industry and OEM specifications required by modern gasoline and diesel power automobile engines.

Benefits

- Excellent shear stability to maintain fluid remains at its grade
- Made of refined base oil and optimized additives reducing the friction between the engine parts.
- Outstanding cleaning performance can prevent ashy build-up under severe operating conditions to prolong engine lifetime
- Provides high performance of engine and contributes to optimized fuel economy

Application

- For all types of modern gasoline and diesel engines
- Use in passenger car and light duty commercial car
- Suitable for engines requiring an API SN, SM, SL or SJ and CF oils

Properties

96 Motor Engine Oil 10W30 has high level thermal stability which ensures the high resistance to oxidation, preventing premature degradation at high temperature. Shear resistance ensuring good lubrication is used, both in hot and cool weather. It is suitable for engines burning Lead free fuel and completely harmless to catalytic convertors.

Typical Characteristics

Motor Engine Oil		Credentials & Specifications
API Grade	SN CF	API: SN CF
Flash Point, °C	257	
Pour Point, °C	-27	
Viscosity at 40°C, cSt	67.04	
Viscosity at 100°C, cSt	10.301	
Viscosity Index	140.08	

Typical physical characteristics of 96 Motor Engine Oil are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Justinjarell Global Sourcing Sdn Bhd
No. 15-2, Jalan Temenggung 27/9,
Mahkota Square, Bandar Mahkota Cheras,
43200 Cheras, Selangor D.E., Malaysia
Tel/Fax: +603 9546 7920
www.96justinjarell.com.my



Furnishing the information contained herein does not constitute a representation by Justinjarell that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Justinjarell or any third party. Justinjarell assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Justinjarell Global Sourcing Sdn Bhd warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.